

# Elda


REKIALIGHT




| | |
|---|---|
| **Product Family** | Elda |
| **Adjustability** | Adjustable: 30°&30° |
| **Color** | White- Black- Gray- RAL |
| **Mounting Type** | Adjustable Recessed Mounted |
| **Body** | Die-cast aluminium body with electrostatic powder coated |
| **Light Source** | COB LED |
| **Color Temperature** | 2700-3000-4000-5000-6500K |
| **Color Rendering Index** | CRI>80,CRI>90 |
| **Power** | 7 W |
| **Power Factor** | Pf>90 |
| **Luminaire Efficiency** | 100lm/W |
| **Light Beam Angle** | 15°,24°,36°,60° |
| **Lumen** | 700 lm |
| **Operating Voltage** | 220-240V AC / 50-60 Hz |
| **Light Source Lifetime** | 50.000 hours Led lifetime |
| **Optic** | High efficiency reflector and PC glass |
| **Control Type** | On/Off – Dali |
| **Electrical Insulation Class** | Class II |
| **Optional Features** | Emergency kit system can be integrated |
| **Sealing** | IP20 |
| **Weight** | 0,45 Kg |
| **Dimensions** | Ø91,5 × 85mm |

**DIMENSIONS**




Lumen value is given according to 4000K value.
Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.
All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.



CE ISO 9001:2015 ISO 14001:2004 5 YEAR WARRANTY