
# Onda 16 MP HB


REKIALIGHT



| | |
|---|---|
| **Product Family** | Onda |
| **Adjustability** | Fixed |
| **Color** | MAT Eloksal |
| **Mounting Type** | |
| **Body** | Extruted aluminium body with electrostatic powder coated |

**DIMENSIONS**





| | |
|---|---|
| **Light Source** | MP LED |
| **Color Temperature** | 2700-3000-4000-5000-6500K |
| **Color Rendering Index** | CRI>80 , CRI>90 |
| **Power** | 145 W |
| **Power Factor** | Pf>90 |
| **Luminaire Efficiency** | 136lm/W |
| **Light Beam Angle** | 30°,60°,90° |
| **Lumen** | 19720 lm |
| **Operating Voltage** | 220-240V AC / 50-60 Hz |
| **Light Source Lifetime** | 50.000 hours Led lifetime |
| **Optic** | High efficiency reflector and extra clear tempered glass |

| | |
|---|---|
| **Control Type** | On/Off |
| **Electrical Insulation Class** | Class I |
| **Optional Features** | Emergency kit system can be integrated |

| | |
|---|---|
| **Sealing** | IP65 |
| **Weight** | 7,1 Kg |
| **Dimensions** | 150 X 70 L: 560 mm |

Lumen value is given according to 5000K value.
Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.
All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.