
Oris – 2 T


REKIALIGHT




Product Family	Oris
Adjustability	Adjustable: 15° & 15° - 355°
Color	White- Black- Gray- RAL
Mounting Type	Trimless Adjustable
Body	Die-cast aluminium body with electrostatic powder coated
Light Source	COB LED
Color Temperature	2700-3000-4000-5000-6500K
Color Rendering Index	CRI>80 , CRI>90
Power	24 W
Power Factor	Pf>90
Luminaire Efficiency	105lm/W
Light Beam Angle	15°,24°,40°,60°
Lumen	2529 lm
Operating Voltage	220-240V AC / 50-60 Hz
Light Source Lifetime	50.000 hours Led lifetime
Optic	High efficiency reflector and PC glass
Control Type	On/Off
Electrical Insulation Class	Class II
Optional Features	Emergency kit system can be integrated
Sealing	IP40
Weight	0,9 Kg
Dimensions	Ø118 × 122 mm

DIMENSIONS







Lumen value is given according to 4000K value.
Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.
All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.

CE ISO 9001:2015 ISO 14001:2004 5 YEAR WARRANTY