
Oris – T

REKIALIGHT




Product Family	Oris
Adjustability	Adjustable: 25° & 25°
Color	White- Black- Gray- RAL
Mounting Type	Trimless Adjustable
Body	Die-cast aluminium body with electrostatic powder coated


Light Source	COB LED
Color Temperature	2700-3000-4000-5000-6500K
Color Rendering Index	CRI>80 , CRI>90
Power	14 W
Power Factor	Pf>90
Luminaire Efficiency	100lm/W
Light Beam Angle	15°,24°,36°,60°
Lumen	1400 lm
Operating Voltage	220-240V AC / 50-60 Hz
Light Source Lifetime	50.000 hours Led lifetime
Optic	High efficiency reflector and PC glass


Control Type	On/Off- Dali
Electrical Insulation Class	Class II
Optional Features	Emergency kit system can be integrated

Sealing	IP20
Weight	0,6 Kg
Dimensions	Ø84,5 × 87mm

DIMENSIONS







Lumen value is given according to 4000K value.
Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.
All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.

CE ISO 9001:2015 ISO 14001:2004 5 YEAR WARRANTY