
# Ovia – 2

REKIALIGHT



| | |
|---|---|
| **Product Family** | Ovia |
| **Adjustability** | Fixed |
| **Color** | White- Black- Gray- RAL |
| **Mounting Type** | Surface Mounted |
| **Body** | |
| **Light Source** | E27 RUSTİK |
| **Color Temperature** | 2500K |
| **Color Rendering Index** | |
| **Power** | 6 W |
| **Power Factor** | Pf>90 |
| **Luminaire Efficiency** | 88lm/W |
| **Light Beam Angle** | |
| **Lumen** | 528 lm |
| **Operating Voltage** | 220-240V AC / 50-60 Hz |
| **Light Source Lifetime** | 50.000 hours Led lifetime |
| **Optic** | |
| **Control Type** | On/Off |
| **Electrical Insulation Class** | Class II |
| **Optional Features** | |
| **Sealing** | IP20 |
| **Weight** | 0,6 Kg |
| **Dimensions** | Ø230 × 172 mm - Ø100 |

**DIMENSIONS**




Lumen value is given according to 2500K value.
Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.
All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.



CE ISO 9001:2015 ISO 14001:2004 5 YEAR WARRANTY